

Full HD Remote Camera with NDI I HX Support

AW-HN130

Full HD Remote Camera with NDI I HX Support



KEY FEATURES

- Built in Support for NDI via NDI|HX
- 1/2.86" 3 MOS Sensor
- 20x Optical Zoom (10x Digital Zoom)
- PoE+ for Single Cable Power, Control, Streaming & Tally
- Video Output: LAN / 3G-SDI / HD-SDI / HDMI / Composite

SPECIFICATIONS

Color	Black (K) or White (W)
Sensor	1/2.86 inch 3MOS
Optical Zoom	20x
i.Zoom	-
Digital Zoom	10x
FOV (Horizontal)	60.2° (W) - 3.3° (T)
FOV (Vertical)	36.2° (W) - 1.9° (T)
FOV (Diagonal)	67.4° (W) - 3.8° (T)
Focus	Auto / Manual
Horizontal Resolution	1000 Lines
Minimum Illumination	2 lx
Gain	0 dB - 36 dB
Power	PoE+ or AC
Installazione	Tripod, Wall*2, Ceiling
Mount Position	Invertible
Standard Warranty	1 Year
Pan Range	±175 degrees
Tilt Range	-30 to 210°
Pan / Tilt Speed	0.08°/s to 60°/s
Operation Noise	NC35 or Less

LAN with built-in NDI HX*1	X
3G-SDI	X
HD-SDI	X
SD-SDI	X
HDMI	X
Composite	X
Output Format	1080/59.94p, 1080/29.97p, 1080/23.98p, 1080/59.94i, 1080/29.97PsF, 1080/23.98PsF, 720/59.94p, 480/59.94p (i)*4, 1080/50p, 1080/25p, 1080/50i, 1080/25PsF, 720/50p, 576/50p (i)*4
Browser (PC/Mac/Mobile) via IP	X
IP Live Preview	X
Simultaneous Multi-Stream	X
Image Stabilization	Optical
Night Mode (for IR)	X
Dynamic Range Stretch (DRS)	X
Audio Input / Embedding	X
Color Temperature Adjustment	X
Presets	Up to 100
Fanless Design	X
ND Filters	X
Genlock	X
Advanced Color Adjustment	X
Digital Noise Reduction (DNR)	X
Note	*1: This product is compatible with NDI HX technology of NewTek, Inc. *2: With appropriate right angle wall mount, available locally *3: HDMI output only. *4: When either 480/59.94p(i) or 576/50p(i) is selected, the output formats are delivered as follows: P signal for HDMI output and I signal for SDI output.
Weight (kg)	Approx. 3.1 kg

URL: <https://business.panasonic.it/telecamere-professionali/aw-hn130>

CONTACT

Enrico Pietrosanti - Via Remo La Valle, 105 - 00054 Fiumicino (Roma)

Tel. 06916505771

Cell. 3406938456

info@enricopietrosanti.com